

# L-864

## Incandescent Red Flashing Beacon



### COMPLIANCES

FAA AC 150/5345 - 43F, L-864

ETL Certified



### PRODUCT APPLICATION

The medium intensity Flashing Red Beacon is used to light aviation obstructions taller than 150 feet AGL.

### SPECIFICATIONS

Horizontal Coverage	360°
Effective Candelas	2,000 ± 20%
Height	30.5 inches (77.47cm)
Flashhead Diameter	16 ½ inches (41.9cm)
Lens Material	Fresnel Pyrex Glass
Base Material	Cast A356 Aluminum
Weight	68 lb (30.9kg)
Power	120VAC or 240VAC; 50/60Hz
Operating Temp	-55 °C to +55 °C
Wind Load	CAAA 1.6 ft2
Lamps	2 - 620W (120VAC) 2 - 700W (240VAC)

6830 NW 16th Terrace • Ft. Lauderdale, FL 33309 USA  
Phone: 1.937.652.3500 • E-mail: AFLsales@HugheyAndPhillips.com  
www.HugheyAndPhillips.com

*Actual product specifications may have changed since the printing of this brochure.  
Brochure specifications are not binding. Confirm current specifications at time of order.*

### AVIATION/OBSTRUCTION LIGHTS - 9.7

### FEATURES

- Porcelain receptacles with nickel plated brass bayonet shell.
- Neoprene and Teflon gaskets for superior weather seal.
- High grade copper free aluminum castings and stainless steel hardware for corrosion protection.
- Stainless steel wingnuts means no special tools required to change bulbs.
- High temperature resistant wire and tie wraps.
- Silicone fused lenses eliminates gasket "dead spot" at light focus.

### ORDERING INFORMATION

Part Number	Description
12001-300mm	Medium intensity flashing beacon, red

*Manufactured by Unimar Lighting & Control Solutions*

### INSTALLATION

Four mounting holes 11/16" spaced 90° on 13 ¼" (33.7cm) bolt circle. 5 foot, 3 or 4 conductor SO Cord pigtail.

